



POWER CONTROLLER QUICK REFERENCE

Style	Maximum Current	Phase	Inputs	Output Mode	Mounting	Operating Environment	Agency Approvals
DIN-A-MITE ®							
Style A	24 amps @ 600VAC	1-phase	VAC/VDC Contactor, 4-20mA	Burst fire	DIN Rail Sub-panel	80°C Max. 0-90% RH Non-Cond.	UL, C-UL VDE
Style B	B 30 amps @ 600VAC	1-phase 3-phase, 2 leg 3-phase, 3 leg	VAC/VDC Contactor, 4-20mA	Burst fire	DIN Rail Sub-panel	80°C Max. 0-90% RH Non-Cond.	UL, C-UL VDE
Style C	65 amps @ 600VAC	1-phase 3-phase, 2 leg 3-phase, 3 leg	VAC/VDC Contactor, 4-20mA	Burst fire Phase angle	DIN Rail Sub-panel	80°C Max. 0-90% RH Non-Cond.	UL, C-UL VDE
Style D	100 amps @ 600VAC	1-phase 3-phase, 2 leg ¹	VAC/VDC Contactor, 4-20mA	Burst fire	Sub-panel	80°C Max. 0-90% RH Non-Cond.	UL, C-UL VDE